

RAYOLITE TEMPLINE WATERBORNE ACRYLIC ROADMARKING PAINT

DESCRIPTION

TEMPLINE has been designed for use where pavement markings are required for a specified period of time. When the pavement markings are no longer required, TEMPLINE can be moved with a low pressure hot water blaster (Class A) resulting in minimal damage to the road surface.

TRANSPORTATION AND HANDLING

TEMPLINE Waterborne Roadmarking Paint is not classified as dangerous goods for Transportation of Dangerous Goods by Rail or Road (ADG Code).

PHYSICAL PROPERTIES

Colours	A range of colours including White, Yellow, Black
Gloss	Matt
Viscosity	95-105 KU @ 25°C
No-pick-time (AS 1580.401.3)	<8 min@50% RH and 25°C
Volume solids	60-62%
Coverage	2.1 sqm/l @ 300 dry film build

APPLICATION AND REMOVAL

For detailed information on the Templine application and removal process refer to the Rayolite Product and Information Procedure Sheet- *TEMPLINE Removable Pavement Marking System*.

The facts stated and the recommendations made are based upon data appraised in our own laboratories and our own research and that of others. Due to possible differences in specifications, application and interpretation of results, no guarantee can be made of these products and they are sold without warranty, express or implied in law or in fact upon the condition that the purchasers make their own test of the products or samples thereof to determine the suitability of the products for the purchasers intended use. Statements concerning the possible use of products or processes are not recommendations or permission to use the same in a manner that would infringe any patent or to practice as patented invention without a licence.

Rayolite Pty Ltd

Address: 237-239 Berkeley Rd, Unanderra, NSW 2526

Postal: PO Box 1156, Unanderra, NSW 2526

Phone: [\(02\) 4271 5056](tel:0242715056)

Mobile: [0407 473 889](tel:0407473889)

Email: sales@rayolite.com.au

Version 1 - July 2025